

# DATASHEET

## SPD030AAHyb Pressure Sensor

last update  
oktober 4, 2016

reference  
spd030aahybsm n

page  
1/1

### SPECIAL ABSOLUTE SENSOR WITH ANALOGUE OUTPUT

This Smartec absolute pressure sensor has an amplified analogue output. The sensor is compensated for offset, sensitivity, temperature drift and nonlinearity. The sensor has a range of 30 PSI FS and the output is ratiometric to the power supply voltage.






### Electrical Characteristics

Performance Characteristic at Vcc =5V excitation @ 25 °C.

Parameter	Min	Typ	Max	Units.
Supply Voltage	4.75	5.00	5.25	V
Supply Current	-	2,5		mA
Pressure range (fs)			30	PSIA
Zero Output (Dif)	0,42	0,5	0,58	Vdc
Span Output (Dif)	3,92	4	4,08	Vdc
Response time		25		ms
Linearity	-0,5		+0,5	%FS
Thermal Hysteresis	-0.1		+0.1	%FS
Temp coeff. Offset	-1		+1,0	%FS
Temp coeff. Span	-1		+1	%FS
Pressure overload			3x	rating
Temp compensation	0		70	°C
Operating Temp range	-20		85	°C
Storage temperature	-40		125	°C

- It is advised to place a 100nF capacitor between Vss and Vdd
- Wetted materials are: Pyrex glass, RTV, Ceramic, Nickel and Silicon
- The output is ratiometric to Vcc

### Dimension



NOTE:  
1. Port B is used for positive differential  
2. Port B is not used for absolute  
3. Port A is not used for gage  
4. All dimension in mm

Use of N.C. pins will cause malfunction  
Connect between Vcc and Gnd a capacitor of 100 nF

Pin	Description
1	NC
2	Gnd
3	Out
4	Vcc
5 - 8	NC